

Общие сравнительные характеристики моделей **INSPUR NF** Rack-серверов на платформе x86
<http://en.inspur.com/inspur/494887/494971/495250/495120/index.html>

Model	U	Type CPU	Socket	Dimm	HDD	RAID	PCI	1Gb	PS	
NF5140M3	1	E5-24** v2	2	12	4*SFF or 4*LFF	Integr SATA	1*8x	2	1	
NF5170M3	1	E5-26** v2	2	20	8*SFF or 4*LFF	Integr SATA	1*16x	2	1 or 2	
NF5240M3	2	E5-24** v2	2	12	24*SFF or 8*LFF	Integr SATA	5	2	1 or 2	
NF5270M3	2	E5-26** v2	2	20	24*SFF or 12*LFF	Integr SATA	3*8x 3*16x	2	1 or 2	
NF5280M3	2	E5-26** v2	2	24	24*SFF or 12*LFF	Integr SATA	6	2	1 or 2	
NF5280M4	2	E5-26** v3	2	24	24*SFF or 12*LFF	Integr SATA	6	2	1 or 2	
NF8420M3	4	E5-46** v2	4	32	16*SFF	Integr SATA	8	2	2 or 4	
NF8460M3	4	E7-48** or 88** v2	4	32	16*SFF	Integr SATA	10	4	2 or 4	